

HIGH WALL



www.patrick-llc.com



- Stylish design & LED display
- Built in EEV, easy to installation
- Negative ion, vitamin C, and ESF filter optional
- EXV Control



Model/Indoor unit			FWH072-AD2	FWH092-AD2	FWH122-AD2	FWH162-AD2	FWH182-AD2	FWH242-AD2	FWH282-AD2	FWH302-AD2
Capacity	Cooling	* kBtu/h	7.9	10.0	12.7	16.1	19.9	25.0	28.1	31.8
		**kBtu/h	7.5	9.5	12.3	15.3	19.1	24.2	27.3	30.7
		** kW	2.2	2.8	3.6	4.5	5.6	7.1	8.0	9.0
	Heating	Btu/h	8.5	10.9	13.6	17.1	21.5	27.3	30.7	34.1
kW		2.5	3.2	4.0	5.0	6.3	8.0	9.0	10.0	
Electrical Parameters	Power supply	Ph/V/Hz	1/220~240/50/60							
	Air flow (H)	m ³ /h	550/480/420	600/530/470	630/560/500	800/720/650	920/800/720	1010/920/800	1500/1400/1300	1600/1500/1400
	Rate Current	A	0.25	0.25	0.25	0.25	0.3	0.3	0.3	0.3
	Rate Power Input	kW	0.05	0.05	0.05	0.05	0.07	0.07	0.07	0.07
Performance	Sound pressure level (H/M/L)	dB (A)	35/31/29	36/31/29	37/33/29	39/36/34	40/39/35	44/40/36	48/43/40	49/44/41
	Sound power level (H/M/L)	dB (A)	50/47/42	52/48/44	54/51/50	56/53/51	57/54/52	58/56/54	60/57/53	61/58/54
	External dimensions (W/D/H)	mm	855/200/280	855/200/280	855/200/280	1115/243/336	1115/243/336	1115/243/336	1316/270/365	1316/270/365
Installation	Shipping dimensions (W/D/H)	mm	954/279/355	954/279/355	954/279/355	1206/342/418	1206/342/418	1206/342/418	1403/384/463	1403/384/463
	Net/Shipping weight	kg	10.5/12.7	10.5/12.7	10.5/12.7	16.5/20.1	16.5/20.1.1	16.5/20.1	21.5/26.0	21.5/26.0
	Refrigerant liquid pipe	mm	6.35	6.35	6.35	6.35	6.35	9.52	9.52	9.52
	Refrigerant gas pipe	mm	9.52	9.52	12.7	12.7	12.7	15.88	15.88	15.88
Controller	Wired (O-Optional/S-Standard)	/	TYR-E16A	TYR-E16A	TYR-E16A	TYR-E16A	TYR-E16A	TYR-E16A	TYR-E16A	TYR-E16A
		/	TYR-E16B	TYR-E16B	TYR-E16B	TYR-E16B	TYR-E16B	TYR-E16B	TYR-E16B	TYR-E16B
		/	TYR-E17	TYR-E17	TYR-E17	TYR-E17	TYR-E17	TYR-E17	TYR-E17	TYR-E17
		/	THW-BA116ABK	THW-BA116ABK	THW-BA116ABK	THW-BA116ABK	THW-BA116ABK	THW-BA116ABK	THW-BA116ABK	THW-BA116ABK
	Infrared (O-Optional/S-Standard)	/	TYR-HD	TYR-HD	TYR-HD	TYR-HD	TYR-HD	TYR-HD	TYR-HD	TYR-HD

Note: 1.* Cooling conditioner : indoor 27°CDB / 19.5°CWB, Outdoor 35°CDB
2.** Cooling conditioner : indoor 27°CDB / 19 °CWB, Outdoor 35°CDB