



THW-BA116ABK TYR-E17 TYR-E16A TYR-E16B

- Variable static pressure 100~200Pa setting
- Install with other indoor units together, and introduce the outdoor fresh air into indoor
- EXV Control



Model/Indoor unit			VFAH48V-AD1	VFAH72V-AD1	VFAH96V-AD1
Capacity	Cooling	kBtu/h	47.7	77.1	95.5
		kW	14	22.6	28
	Heating	Btu/h	30.4	51.8	60.8
		kW	8.9	15.2	17.8
Electrical Parameters	Power supply	Ph/V/Hz	1/220~230/50/60	1/220~230/50/60	1/220~230/50/60
	Rate Current	A	2.5	3.3	4.0
	Rate Power Input	W	560	730	870
Performance	Air flow (H)	m <sup>3</sup> /h	1600	2300	2800
	Sound pressure level(H/M/L)	dB(A)	48	55	55
	Sound power level(H/M/L)	dB(A)	61	68	68
Installation	External dimensions(W/D/H)	mm	1355/876/360	1725/876/360	1725/876/360
	Shipping dimensions(W/D/H)	mm	1386/966/418	1830/990/530	1830/990/530
	Net/Shipping weight	kg	62/77	92/100	92/100
	Refrigerant liquid pipe	mm	9.52	9.52	9.52
	Refrigerant gas pipe	mm	15.88	25.4	25.4
	Static Pressure(Standard/Max.)	Pa	100/185	100/200	100/200
Controller	Wired (Optional)	/	TYR-E16A	TYR-E16A	TYR-E16A
		/	TYR-E16B	TYR-E16B	TYR-E16B
		/	THW-BA116ABK	THW-BA116ABK	THW-BA116ABK
		/	TYR-E17	TYR-E17	TYR-E17